



Lounge chair with upholstered shell, aluminum arms with upholstered top face and steel sled base finished in polished chrome, white or black.

📦 0.56 m³ 📏 19.78 Ft 📊 28 kg 📊 61.73 Lbs 📏

| | Backrest height | Seat height | Arm height | Width | Depth |
|----------------------|-----------------|-------------|------------|-------|-------|
| Measures (mm) | 820 | 420 | 610 | 790 | 780 |

Fabrics / Telas

- 1** Soft-fiber
Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2** Jacquard Two
Loom One
Circular One Pure Eco
- 3** Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo

- 4** Jacquard 4 Special
Nexus
Field 2
Floyd
Remix 3
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5** Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6** Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7** Canvas 2
Rime
Select
Clara 2
- 8** Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9** Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1** Valencia
2 Silvertex
3 Maglia
4 Dolce
8 Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9** Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10** Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired

- 11** Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Upholstery

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Steel finish



Aluminum finish

| | |
|-------------------------------|---|
| RESISTANCE AND QUALITY | UNE-EN 16139:2013 ISO 9001 |
| FIREPROOF | UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V UNI 9175 M-1 California Tech.Bulletin 117 |
| SUSTAINABILITY | ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard |