



Chair with upholstered seat and backrest and 4 solid beech wood legs.

0.33 m³ 10.6 kg
11.65 Ft 23.37 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	835	460	560	620

Seat Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 25 kg/m³ and 40 kg/m³.

Back Beech plywood shell with flexible flame retardant foam with density between 25 kg/m³ and 40 kg/m³.

Accessories Polypropylene, felt or steel glides.

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2 Jacquard Two
Solid & Stripes
Loom One
Circular One Pure Eco
- 3 Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo

- 4 Jacquard 4 Special
Nexus
Field 2
Floyd
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic

- 5 Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6 Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7 Canvas 2
Rime
Select
Clara 2

- 8 Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino

- 9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
- 2 Silvertex
- 3 Maglia
- 4 Dolce
- 8 Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9 Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10 Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired


- 11 Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Upholstery

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Wood finish Beech



Premium finish and wood lacquers



RESISTANCE AND QUALITY

UNE-EN 16139:2013
ISO 9001

FIREPROOF

UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY

FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard