



Armchair with solid beech wood seat and backrest and steel sled base and finished in polished chrome, white or black. Optional removable upholstered seat cushion.

📦 0.34 m³ 📏 12.01 Ft ⚖️ 10.58 kg 📏 23.32 Lbs 📏

	Backrest height	Seat height	Width	Depth
Measures (mm)	860	460	640	535

Frame	Sled base of 12 mm diameter steel rod. Polypropylene glides.
Seat	Upholstered seat cushion fixed on solid beech.
Back	Solid beech.
Arms	Solid beech.
Accessories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Upholstery

Fabrics / Telas

- 1** Soft-fiber
Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2** Jacquard Two
Solid & Stripes
Loom One
Circular One Pure Eco
- 3** Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo
- 4** Jacquard 4 Special
Nexus
Field 2
Floyd
Remix 3
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5** Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool
- 6** Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7** Canvas 2
Rime
Select
Clara 2
- 8** Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9** Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1** Valencia
- 2** Silvertex
- 3** Maglia
- 4** Dolce
- 8** Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9** Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10** Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired
- 11** Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Leather

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Wood finish Beech



Premium finish and wood lacquers



Steel finish



RESISTANCE AND QUALITY

UNE-EN 16139:2013
ISO 9001

FIREPROOF

UNE-EN 1021-1:2006

B.S. 5852 Part 2 Crib V

UNI 9175 M-1

California Tech.Bulletin 117

BKZ 5.2

SUSTAINABILITY

FSC

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard