



Chair with upholstered seat and backrest and solid ash wood frame.

0.338 m³ 9 kg
11.94 Ft 19.84 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	775	455	700	640	565

Frame	Solid ash legs and frame.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Accessories	Polypropylene, felt or steel glides.
Other materials	Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1 Soft-fiber
Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2 Jacquard Two
Solid & Stripes
Loom One
Circular One Pure Eco
- 3 Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo

- 4 Jacquard 4 Special
Nexus
Field 2
Floyd
Remix 3
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5 Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6 Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7 Canvas 2
Rime
Select
Clara 2
- 8 Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
- 2 Silvertex
- 3 Maglia
- 4 Dolce
- 8 Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9 Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10 Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired

- 11 Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Upholstery


Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



**Premium finish
and wood
lacquers**



Wood finish Ash



**RESISTANCE AND
QUALITY**

UNE-EN 16139:2013
 ISO 9001

FIREPROOF

UNE-EN 1021-1:2006
 B.S. 5852 Part 2 Crib V
 UNI 9175 M-1
 California Tech.Bulletin 117

SUSTAINABILITY

FSC
 ISO 14001
 level® 2 certified to ANSI/BIFMA e3 Standard