



Low back armchair with upholstered shell and Eco thermo-polymer central base with 5 casters, swivel and pneumatic height adjustment, finished in black. Available options: Parallel upholstery stitching, tilting mechanism and back finished in walnut veneer.

0.33 m3 11.65 Ft 13.52 kg 29.81 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	835	440	650	665	615

Fabrics / Telas

- 1** Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban
- 2** Jacquard Two
*Loom One
Circular One Pure Eco
- 3** Jacquard Four
Medley
Revive 1
Main Line Flax
Loom Two
Mezzo

- 4** Jacquard 4 Special
Nexus
Floyd
*Remix 3
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5** Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6** Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7** Canvas 2
Rime
Select
Clara 2
- 8** Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9** Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1** Valencia
- 2** Silvertex
- 3** Maglia
- 8** Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9** Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10** Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired

- 11** Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

* Only available with parallel stitching upholstery.
 Solo en tapizado con costuras paralelas.

Upholstery

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



**Eco Thermo-
polymer finish**

RESISTANCE AND QUALITY	UNE-EN 16139:2013 ISO 9001
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard